

### Series Features



- 120/277 VAC Input
- Light-Emitting Diodes
- Illuminates with Uniform Color and Brightness
- Directly Viewed LEDs have 100–300 Foot Visibility
- 25+ Year Life (No Relamping)



- Rugged 16-Gauge Housing
- Polycarbonate Face Shield
- Tamper-Proof Screws
- Canopy Factory Attached (Specify Location)
- White Powder-Coat Finish
- Meets or Exceeds UL Standards

### Additional Emergency Unit Features



- Integrated Solid State System
- Constant Current, Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- AC Lockout (Line Latching)



- Sealed Nickel Cadmium Battery
- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free



- Increased Illumination During Power Failure
- Test Switch
- Power On Indicator LED Lamp

### Diffused LED Rating



- Maximum Input Rating (120 or 277VAC)
 

Standard	1.7 Watts
DS Option	3.5 Watts
- 3+ Hours Illumination in Emergency Mode

### Direct View LED Rating



- Maximum Input Rating (120 or 277VAC)
 

AC Only	Single Face	3.6 Watts
	Double Face	5.6 Watts
Emergency	Single Face	6.8 Watts
	Double Face	8.0 Watts
- 3+ Hours Illumination in Emergency Mode (Single)
- 1.5 Hours Illumination in Emergency Mode (Double)

## AL-75746



### Options

Add Suffix to Catalog Number

- 2CKT (2) Independent AC Circuits (VRXL Only)
- BZ Audible Buzzer in Emergency Mode (EVRXD Only)
- DL Downlight LED (VRXD/EVRXD Only)
- DMP Damp Location Listing (Damp Label)
- DS Double LED Strips for Increased Illumination or 2 Independent AC Circuit Operation
- FAI Fire Alarm Interface
- FL Flasher in Emergency Mode (EVRXD Only)
- HI High-Intensity LEDs
- HTR Heater

### Dimensions

VRX/EVRX  
 Height: 7.7"  
 Width: 12.5"  
 Depth: 2.7"



Made in USA

### Ordering Information

AL-75746	L	1	R	W	W	-DS
Series	LED Type	# Faces	Letter Color	Stencil Color	Housing Color	Options
VRX – AC Only EVRX – Emer.	L – Diffused D – Direct View	1 2	R ed G reen	W hite B lack PM-Painted Matte Chrome	W hite B lack PM-Painted Matte Chrome	Factory Options