



TECHNICAL SPECIFICATIONS

TEN to SIXTY LAMP ANNUNCIATOR PANEL

AL-84670

ALCO
Sales & Service Co.



DESCRIPTION

Wall recessed or surface mounted ten-to-sixty lamp call annunciator panel providing visual system status indication via ten-to-sixty lamp positions.

INDICATORS

Ten-to-sixty low-power high visibility lamps. Standard lens color is white, others available separately include: red, amber, green, blue, yellow and clear.

Custom laminated labels are available for lenses. Lamps are rated 24 VDC at 40 mA. Lamps are front replaceable with rated average life of 6000 hours.

LISTINGS

The AL-84670 is UL and CUL listed Hospital Signaling Equipment / Nurse Call Equipment under File E157381.

INSTALLATION

Plugs into prewired connectors.
AL-84670 requires one prewired connector (included)

Mounts onto backbox with four 6-32 x 1" nylon screws provided.

HOUSING AND FINISH

Faceplate: Flame retardant ABS plastic rated 94V-O by UL, finished in off-white and supplied with nylon mounting screws.

DIMENSIONS

10 Lamp Faceplate: 6-3/8" wide x 4-1/2" high.

Backbox: 5-3/4" wide by 4" high electrical backbox with three gang adapter for total depth of 3-5/16", supplied by others.

20 - 60 Lamp Faceplate: 8-1/2" wide x 11" high.

W2 Backbox: 7-1/2" wide x 10" high x 3 1/2" deep

ARCHITECTS' AND ENGINEERS' SPECIFICATIONS

MODEL AL-84670 TEN-to-SIXTY POSITION ANNUNCIATOR PANEL

The wall recessed or surface mounted AL-84670 Ten-to-Sixty Position Annunciator Panel shall provide visual status indication via 10-60 lamp positions.

The panel shall provide ten-to-sixty low-power high-visibility indicator lamps. Lamps shall be front panel replaceable with an average rated life of 6000 hours. Standard lens color shall be white. Others lens colors available separately shall be red, amber, green, blue, yellow, and clear.

The AL-84670 is UL and CUL listed Hospital Signaling Equipment / Nurse Call Equipment under File E157381.

The faceplate shall be flame retardant ABS plastic rated 94V-O by UL, finished in off-white and supplied with nylon mounting screws.

Faceplate shall mount to backbox with four 6-32 x 1" nylon screws provided.

Annunciator panel shall install into a three gang box with a three gang adapter for surface or wall flush mounting. The dimensions shall be: **Faceplate** - 6-3/8" (16.19cm) wide x 4-1/2" (11.43cm) high; **Backbox**: 5-3/4" (14.6cm) wide by 4" (10.16cm) high electrical backbox with three gang adapter for total depth of 3-5/16" (8.41cm), supplied by others.

