

ASSEMBLY INSTRUCTIONS

APPLIES TO:

Some Large Capacity Laundry Carts

AL-51303
AL-55152

AL-51304
AL-55153

PLEASE MAKE SURE ALL NUTS AND BOLTS ARE SECURE BEFORE PLACING CART INTO SERVICE.



Caster & Base Assembly

- 1 Place raceway guards (4) onto each caster
- 2 Insert casters (4) into the base legs
- 3 Insert 1 % " bolts through caster & base hole
- 4 Secure with 1/2" nylon lock nuts



Basket & Base/Caster Assembly

- Place basket on top of base/casters and Align holes on basket with holes on base
- 2 Insert 1 $\frac{1}{2}$ " bolts through basket and base
- Secure with 1/4" nylon lock nuts
- 4 If no pole rack is to be installed, tighten bolts securely
- 5 If a pole rack is to be installed, only finger tighten the basket to base/casters and proceed to step 3
- 4 Tighten all bolts securely

x2 double chrome tubes

x1 crossbar

x4 bolts

o x4 nuts



Double Pole Rack Assembly

- Place long rack tubes (2) through inside of basket
- 2 Insert long hex head bolts (4) through long rack tubes (2) and cart secure with nuts (4)
- 3 Attach crossbar to long rack poles by inserting short hex head bolts through crossbar and long rack tube's holes, secure w/nuts(2)
- 4 Tighten all bolts securely



- inside of basket
- 2 Insert long hex head bolts (2) through long rack tube and cart secure with nuts (2)
- 3 Attach arm to long rack tube by inserting short hex head bolt through arm and long rack tube, secure with nut
 - *Be sure arm faces toward center of basket

PARTS INCLUDED for SOME CARTS AND RACKS **x8** 11/8" bolts • x12 1/4" nylon lock nuts x4 11/2" bolts x1 200 series basket x4 raceway guards 💰 x4 5" casters





