

Plastic Diffused LED Exits & Two-Headed Combo LED Exits

Series Features



- 120/277 VAC Operation
- Maximum Input Rating (120 or 277VAC) 1.7 Watts Standard



- Light-Emitting Diodes – 25+ Year Life
- Illuminates with Uniform Color and Brightness
- Indirect Placement for Diffused Legend Output



- Ceiling, End or Back Mount
- Canopy
- Universal Stencil
- Directional Chevron Snapouts
- White Finish
- Easy Installation
- UL Listed
- Flame-Retardant, High-Impact, Thermoplastic Housing
- Damp Location

Additional Emergency Unit Features



- Integrated Solid State System
- Constant Current, Controlled Automatic Charger Circuit
- Low-Voltage Battery Cutoff
- Brownout Sensitivity



- Initial Increased LED Brightness Level in Emergency Mode
- 2EXKL: (2) 6W Adjustable Lamp Heads



- EXKL: Sealed Nickel Cadmium Battery
- 10-Year Battery Warranty
- 2EXKL: Sealed Lead Cadmium Battery
- 5-Year Battery Warranty



- Test Switch
- LED (Power On) Indicator

Ordering Information

EXKL	1	R	W	W	U	-SD
Series	# Faces	Letter Color	Stencil Color	Housing Color	Universal	Options
AL-52099- AC Only	2	Red	White	White	Single- or Double-Face	Factory Options
AL-52100- Emer		Green				
AL-75744 - Combo						

AL-52099



AL-75744



Options

Add Suffix to Catalog Number

For 75744 Only

- BLK Black Housing
- RMT Remote Capability Additional 12 Watts at 6VDC for the 2DZF-PAR
- SD Self Diagnostic
- SALIDA Spanish "SALIDA" Exit Sign

Dimensions

52099

Height: 8.75
Width: 12.25"
Depth: 2.5"

2EXKL

With Heads on Side
Height: 10.2"
Width: 21.7"
Depth: 4.5"

With Heads on Top
Height: 15.7"
Width: 16.3
Depth: 4.5"



UL 924 LISTED

ALCO
Sales & Service Co.

800.323.4282
www.alcosales.com