

6851 High Grove Blvd. Burr Ridge, IL 60527 Phone: (800) 323-4282 Fax: (800) 950-1167 www.akosales.com

Commercial-Grade Surge Suppressor with Hospital-Grade plug and receptacles; diagnostic LEDs and a heavy-duty metal housing

MODEL NUMBER: AL-54227









Highlights

- · 6 hospital-grade outlets
- 1050 joule rating
- 15-ft. cord with molded hospital-grade plug
- · All metal housing

Applications

 AC power distribution and surge suppression with hospital-grade receptacles and plug where durability and reliability are required. Not for use where NEC requires hospital-grade receptacles.

Package Includes

- · AL-54227 Surge Suppressor
- Instruction manual with warranty information

Description

ALCO State AL-54227 often 154-capacity AC surge suppression and power distribution in a ruggest all-inetial cultet strip for 120V applications. Offen 6 AC outlets. 154 AL Cover cort, built in restantial circuit breaker and to 000-public AL surge pospression. Features and stresh e-manace hospital grade plag and outlets. StefAL Source cort, built in restantial abudit () optional use keyhole mounting tabs. 15A circuit breaker controls power to all cultets and protects stanta venticabat. EDFoddator writerilis and power available.

PLUG/OUTLETS: NEMA 5-15PHG Hospital-Grade Plug and 6 x NEMA 5-15RHG Hospital-Grade AC Outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet surge suppression strip

SUPPRESSION: AC: 150V RMS Clamping/1050 joules

Features

- · 1050-joule AC surge suppression rating
- · Rugged all-metal housing withstands years of use without loss of ground path continuity
- · 6 NEMA5-15R Hospital-Grad AC outlets
- · 15-ft. AC cord with integrated, molded Hospital-Grade NEMA 5-15PHG plug
- · Keyhole mounting tabs and flanges
- · Switch safety cover prevents accidental shutoff
- · 15A electrical capacity with built-in resettable circuit breaker
- · 120 volt, 50/60Hz electrical compatibility
- · Certified by UL (USA) and cUL (Canada)
- · UL1449 3rd Edition listed



Specifications

OVERVIEW		
Intended Application	Hospital/Medical	
Model Type	NOT For Patient Areas	
OUTPUT		
Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Circuit Breaker (amps)	15	
Outlet quantity / type	6 NEMA 5-15R-HG	
Transformer accommodation	Supports 1 large transformer plug accessories without covering remaining outlets	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P-HG Hospital-Grade	
Input cord length (ft.)	15	
Input cord length (m)	4.6	
Voltage compatibility (VAC)	120	
Maximum Surge Amps	19500	
LEDS ALARMS & SWITCHES		
Diagnostic LEDs	LINE POWER PRESENT (green)	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	1050	
AC suppression response time	< 1 ns	
Protection modes	Includes full normal mode surge suppression	
Clamping voltage (RMS)	140V	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		



Shipping Dimensions (HWD/in)	2.25 x 15 x 6	
Shipping Dimensions (HWD/cm)	5.7 x 38.1 x 15.24	
Shipping weight (lbs)	3.5	
Shipping weight (kg)	1.59	
Unit Dimensions (HWD/in)	1.5 x 13.75 x 2.5	
Unit Dimensions (HWD/cm)	3.81 x 34.9 x 6.35	
Unit weight (lbs)	3.2	
Unit weight (kg)	1.45	
Material of construction	Metal	
Integrated keyhole mounting tabs	Includes keyhole mounting tabs and flanges	
Receptacle Color	White	
AC line cord color	Gray	
Style	Strip	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd Edition	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

ALCO Sales. All rights reserved. All trademarks are the sole property of their respective owners. ALCO Sales has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.