

NOT For Patient Areas - 1U Rackmount Power Strip with 12 Hospital-Grade Outlets and 15-ft. Cord

MODEL NUMBER: AL-59794



Description

ALCO Saye AL-26754 al-metal Pover Ship often 154 Capacity AC pover distribution in a versatiletie multi-mount calative. Detahable mountime finges are configurate for raxhomuru, with without and under-courter installation. Uses only 1 rack space (1U) when installed in any 154-n rack meeting ELA standards. Uniffered edicical gass-through markes the RS-121-164 Galad for distributing alternate waveform UPS or generator pover in rack enclosures, metwork colests and more. Features foopbal Grade plug and outlest. Includes 12 outlets (6 fronts frav, 154-AC opvec ord and lighted workh mit pover to prevent accident lam-off.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 12 NEMA 5-15R-HG hospital-grade outlets (6 front/6 rear)

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: 19-in. rackmount (1U)

Features

- · Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting options
- · Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- · Uses one rack space (1U) in standard 19-in. rack ("zero U" mounting possible in many racks)
- . 12 x NEMA 5-15R-HG hospital-grade output receptacles (6 front/6 rear), each pair with green-dot hospital-grade designation
- . 15-ft. 14-gauge AC cord with high-impact resistant NEMA 5-15P-HG hospital-grade plug
- · Lighted power switch (with safety cover) confirms power on/off status
- · Snap-in switch guard prevents accidental turn-off
- · 15A electrical capacity with resettable circuit breaker
- 120V AC, 50/60Hz electrical compatibility

Specifications

Highlights

- Designed for standard 19-inch racks (1U high)
- 12 hospital-grade outlets (6 front / 6 rear)
- 15-ft. cord with hospital-grade plug
- 15A resettable circuit breaker
- Illuminated On/Off switch with locking safety cover

Applications

 AC power distribution with hospital-grade receptacles and plug where durability and reliability are required. Not for use where NEC requires hospital-grade receptacles.

Package Includes

- AL-59794 Rackmount Power Strip
- Instruction manual with warranty information



Intended Application	Hospital/Medical
Model Type	NOT For Patient Areas
OUTPUT	
Frequency compatibility	50 / 60 Hz
Circuit Breaker (amps)	15
Outlet quantity / type	12 NEMA 5-15R-HG
Outlet orientation	6 front / 6 rear
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A 120V
Input connection type	NEMA 5-15P-HG
Input cord length (ft.)	15
Input cord length (m)	4.572
Voltage compatibility (VAC)	120
LEDS ALARMS & SWITCHES	
Switches	Red illuminated 2 positon switch controls power to all outlets
Locking switch cover	Transparent locking switch cover prevents accidental shutoff
PHYSICAL	
PHYSICAL Unit Dimensions (HWD/in)	1.75 x 17.3 x 4
	1.75 x 17.3 x 4 4.4 x 43.9 x 10.2
Unit Dimensions (HWD/in)	
Unit Dimensions (HWD/in) Unit Dimensions (HWD/cm)	4.4 x 43.9 x 10.2
Unit Dimensions (HWD/in) Unit Dimensions (HWD/cm) Unit weight (lbs)	4.4 x 43.9 x 10.2 4.6
Unit Dimensions (HWD/in) Unit Dimensions (HWD/cm) Unit weight (lbs) Unit weight (kg)	44 x439 x102 48 2.09
Unit Dimensions (HWD/in) Unit Dimensions (HWD/cm) Unit weight (Ibs) Unit weight (kg) Material of construction	4.4 x 43 9 x 10.2 4.6 2.00 Sheet metal
Unit Dimensions (HWD/in) Unit Dimensions (HWD/cm) Unit weight (bs) Unit weight (kg) Material of construction Receptacle Color	4.4 x43 9 x10 2 4.6 2.00 Shed metal White
Unit Dimensions (HWDlin) Unit Dimensions (HWDlom) Unit weight (bs) Unit weight (kg) Material of construction Receptacle Color AC line cord color	44 x43 x10 2 4.0 2.06 Shed metal White Black



TVSS grounding	Back panel nut and bolt grounding lug	
CERTIFICATIONS		
UL1363 (Power Tap)	UL1363 (UR status)	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

ALCO Sales. All rights reserved. All trademarks are the sole property of their respective owners. ALCO Sales has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.