


ANTI-LIGATURE TOILET PAPER HOLDER CONCEALED MOUNTING



Construction:

FLANGE: 11 GAUGE X 3" DIAMETER TYPE 304 STAINLESS STEEL
ROD: 1/2"Ø STAINLESS STEEL ROD WITH PIVOTING JOINT THAT
RELEASES UNDER EXCESSIVE LOAD.
TEE NUTS: (2) 1/4"-20 STAINLESS STEEL WELDED TO BACK OF
FLANGE.

Operation:

ROD WITH PIVOTING BALL JOINT RELEASES WHEN EXCESSIVE LOAD IS APPLIED.
ROD IS RESET BY HAND WHEN REQUIRED.

Installation:

MARK HOLES AT DESIRED HEIGHT AND ON 2IN. CENTERS. DRILL HOLES FOR 1/4" WALL STUDS
NOT INCLUDED.
INSERT WALL STUDS THROUGH THE HOLES AND THREAD INTO TEE-NUTS.
FASTEN WITH WASHER AND NUTS.
ACCESS IS REQUIRED TO BACK OF WALL.
CUT WALL STUDS LONG ENOUGH FOR WALL THICKNESS, THREAD ENGAGEMENT, WASHERS AND NUTS.

Guide Specification:

HOLDS ONE STANDARD 5 IN.Ø X 4 1/2" LONG TOILET TISSUE ROLL.
CONCEALED MOUNTING.
ROD RELEASES WHEN EXCESSIVE LOAD IS APPLIED.
ONE PIECE ANTI-LIGATURE CONSTRUCTION, SATIN #4 FINISH.

Mfg. reserves the right to
make changes in design and/or
material without formal notice and
without incurring any obligation.

ALCO Sales & Service Co.

6851 High Grove Blvd., Burr Ridge, IL 60527
Phone: 800.323.4282 Fax: 800.950.1167
www.alcosales.com info@alcosales.com