

6851 High Grove Blvd. Burr Ridge, IL 60527 Phone: (800) 323-4282 Fax: (800) 950-1167 www.alcosales.com

For Patient-Care Areas - 4-outlet Medical-Grade Power Strip with 3-ft. Coiled Cord (Extends to 10 Feet)

MODEL NUMBER: AL-81559









Description

ALCO Sales AL:B1559 Power Strip is designed to be installed on any mobile cart, diagnostic equipment, instrument, IV pole, etc. II:s TUV tested to UL. 353A to supply power to plug-connected components of a movel be equipment assembly that is not, table or pedestain-mounted. Features 4 output receptades, 34. AC colled cord (extends to 10-4) and two built-in resettable circuit breakers that control power to all outlets and protect against evertoads. Switchless design prevents accidental shubff. Optional-use keyhole mounting table and farges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 4 NEMA5-15R-HG hospital-grade receptacles ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal coil corded multi-outlet strip.

Features

- · Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- . TUV tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- · 4 x NEMA 5-15R-HG hospital-grade output receptacles
- · 3-ft. AC coiled cord (extends to 10-ft.) with integrated, molded NEMA5-15P-HG hospital-grade plug
- · Rugged all-metal housing withstands years of use without breakage
- · 15A electrical capacity with two built-in resettable circuit breakers
- 120V, 50/60Hz
- · Optional-use keyhole mounting tabs and flanges
- · Switchless design prevents accidental shutoff

Specifications

Highlights

- Versatile power distribution strip designed to be installed on any mobile cart, IV pole, etc.
- Tested to UL 1363A to supply power to plug-connected components of a movable equipment assembly that is rack-, table- or pedestal-mounted
- 4 hospital-grade receptacles and hospital-grade plug
- · 3-ft coiled cord, extends to 10-ft.
- Two 15-amp resettable circuit breakers

Applications

- Mobile carts, IV poles and other UL 1363A certified usages.
- Can be used in Patient Care Areas, when properly mounted.

Package Includes

- AL-81599 Power Strip
- Owner's manual and warranty information



OVERVIEW	
Intended Application	Hospital/Medical
Model Type	For Patient-Care Areas
OUTPUT	
Frequency compatibility	50 / 60 Hz
Circuit Breaker (amps)	15
Overload protection	2 x 15amp breakers (1 line, 1 neutral)
Outlet quantity / type	4 NEMA 5-15R-HG
Outlet orientation	Single row of 4
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A, 120V
Input connection type	NEMA 5-15P-HG
Input cord length (ft.)	10
Input cord length (m)	4.572
Input cord gauge, type	14 gauge, SJT
Voltage compatibility (VAC)	120
LEDS ALARMS & SWITCHES	
Switches	No power switch
PHYSICAL	
Shipping Dimensions (HWD/in)	2.44 x 6.18 x 9.92
Shipping Dimensions (HWD/cm)	6.19 x 15.7 x 25.2
Shipping weight (lbs)	2.4
Shipping weight (kg)	1.09
Unit Dimensions (HWD/in)	1.73 x 2.50 x 8.54
Unit Dimensions (HWD/cm)	4.39 x 6.35 x 21.69
Unit weight (lbs)	2.2
Unit weight (kg)	1.0
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
Receptacle Color	White



AC line cord color	White	
Style	Strip	
Outlets center to center measurement	77.60mm	
Keyhole slot center to center measurement	Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm	
CERTIFICATIONS		
Approvals	TUV tested to UL 1363A	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

ALCO Sales. All rights reserved. All trademarks are the sole property of their respective owners. ALCO Sales has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.