

TIMELESS DESIGN. ENDLESS APPLICATIONS.



AL-82859

Call for black

DIAMOND SERIES

The world's most popular guestroom telephone.

Teledex Diamond Series

- Single and Two-Line Telephone
- Integrated Speakerphone – Hands-free conversations*
- Guest Service Buttons – Up to ten (10) for one-touch access to hotel services
- ADA Handset Volume Boost – Three (3) distinct levels, compliant with HAC/VC and FCC requirements
- Raised Red Message-Waiting Lens – Easily seen from any area in the guestroom
- Message-Waiting Circuitry – Message Waiting will activate on high or low voltage; Guarantees operation of up to 7 phones for suite applications, with an extra-bright message-waiting lamp
- Mute Key – Deactivates microphone during speakerphone and handset calls; a red LED indicates activation**
- Speaker On/Off Key – With red LED for easy speakerphone activation*
- Electronic 3-way Call Conference Function with LED indicator for convenient multi-line conversations***
- Hold Key – Places the active line on hold so the second line can be used or a conference call initiated***
- Hold Release Detection Circuit – Releases calls on hold when line is accessed by any telephone

- Redial Key – Automatically redials the last number dialed, with timed deletion of the last number after 30 minutes for enhanced hospitality security (most models)
- Flash Key (most models)
- Textured Finish – Provides durable resistance against scratches and smudges
- Full-Length Paper Faceplate – Allows user-friendly customization
- Desk or Wall Mountable – Provides placement flexibility
- Hidden Programming Key – Eliminates arbitrary reprogramming of autodial keys
- Data Port – Easy access for laptop modem or fax machine use

*Speakerphone models only

**Not available in single-line basic or lobby phones

***Two-line only



Call for black

TELEDEx DIAMOND SERIES

SPECIFICATIONS

| | |
|----------------------------|--|
| Standard Color: | Ash and Black |
| Footprint (Desk): | 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 2.5" (6.35cm) (d) (without handset); 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 3.75" (9.53cm) (d) (with handset) |
| Footprint (Wall): | 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 2.13" (5.41cm) (d) (without handset); 6.25" (15.88cm) (w) x 9.5" (24.13cm) (l) x 3.25" (8.23cm) (d) (with handset) |
| Weight: | 1.85 lbs. (0.83kg) |
| Packaging: | 10 per carton |
| Faceplate Size: | 3.13" (w) x 8.75" (l) |
| FCC Specifications: | Meet or exceeds Part 15, Subpart J, Class A, Part 68 |
| Safety Standard: | ETL and CE |

| | |
|------------------------------|--|
| Operating Voltage: | 24 to 56 VDC Non-Polarity |
| Signaling: | Standard 12 tone DTMF no Pulse/Rotary dialing |
| Flash Timing: | 100 mS to 1000mS |
| Ringer Equivalence: | Z |
| Cabling: | 2 pair minimum |
| Registered Connector: | USOC RJ-14 |
| Handset: | Hearing Aid compatible Standard "K" type |
| Handset Cord: | 10-foot coil cord |
| Line Cord: | 12-foot, 2 pair |

AL-82859

ALCO
Sales & Service Co.

info@alcosales.com | 800.323.4282 | www.alcosales.com

