

Features

- UL[®] 1069 Listed
- Snap-in lens
- Easy bulb replacement
- Attractive flame-retardant HIPS30 plastic panel
- Excellent visibility

Description

The AL-59582 Corridor Light and Corridor Zone Light provide visual indication of calls when used with a nurse call system, emergency call system, or similar application. Emergency calls are indicated by the rapid flashing of the Corridor Light associated with the calling station. Normal calls produce a steady illumination.

The standard mounting plate features an easily removable white flame-retardant translucent polystyrene plastic lens for bulb replacement.



AL-59582 - Corridor Light

Listings



UL[®] 1069 listed; UL[®] File Number E71599.

Specifications

Dimensions:	Height:	4.5625"	(115 mm)
	Width:	4.5625"	(115 mm)
	Depth:	3.3"	(84 mm)
Bulbs:	#1829 28V 70 mA		
Power:	LI381:	24 VDC or VAC, 51mA	
	LI382:	24 VDC or VAC, 102mA	
Finish:	White flame-retardant translucent polystyrene plastic lens mounted on a flame-retardant (UL [®] 94V-0) plastic panel.		
Housing:	Fits either standard dual gang box and ring or single gang box and ring.		

Applicable Systems

Tek-CARE[®] NC110, NC150, NC200 or NC300II Nurse Call System

Tek-CARE[®]500 Wireless Emergency Call System with NC50xES-series remote receiver
CM800 Emergency Call System