

Ektacom/Fisher-Berkley Nurse Call Dual Patient Station

AL-65962

DESCRIPTION

The ALCO AL-65962 Dual Bedside Station is designed for flush mounting in two bed locations, and incorporates the latest state-of-theart components for maximum life and minimum maintenance.

The AL-65962 provides instant patient call registration upon momentary activation of the patient's cordset. The call remains registered until reset at the AL-65962 or until answered from the Nurse Control Station.


A sensitive speaker-microphone permits two-way voice communication between the AL-65962 and the Nurse Control Station without the patient having to raise his voice or turn towards the bedside station. A yellow MONITOR LED illuminates whenever the Nurse Control Station is monitoring the patient's room.

The AL-65962 utilizes a unique circuit that completely avoids the use of mechanical relays found in competitive units; further, this circuit uses a minimum number of active components. Both of these design features insure maximum reliability and extra long life. Light Emitting Diodes (LED) help reduce maintenance to a minimum.

A stainless steel panel is used with each functional component clearly identified as to function. The design permits mounting in standard electrical backboxes.

SPECIFICATIONS

Circuits: all solid state (no relays)
Controls: RESET button (Momentary)
Indicators: Call, red LED; MONITOR,
yellow LED. Life greatly exceeds that
of incandescent lamps.



AL-65962

SPECIFICATIONS (continued)

Receptacles: Octal, compatible with all standard eight-pin cordsets.

Speaker-Microphone: 2"diameter, dynamic transducer, low impedance balanced line for minimal noise.

Panel Dimensions: 6.7"wide x 4.5"high Backbox: Steel City 3G 1/2 or 3G 3/4 with 3GC plaster ring or exact equal. Do not use bottom knockouts.

Faceplate: type 30 2 stainless steel, horizontal grain, with baked epoxy

FEATURES

+ Simple, Basic Operation

nomenclature.

- + Automatic Call Placement upon removal of call cord
- + All Solid-State Circuits
- + LED Indicators
- + Stainless Steel Faceplate
- + Standard Electrical Box Mounting
- + Uses Standard EKTACOM Cordsets
- + Low Maintenance
- + Only Six Field Wiring Connections
- + Patient Reminder and Parallel Nurse Annunciation Circuits Available
- + Uses UL 1069 Listed Power Supply