

6-Outlet, 6-ft-Cord Surge Suppressor with Right-Angle Hospital-Grade Plug and Receptacles

MODEL NUMBER: **AL-81561**



Highlights

- 6 hospital-grade outlets
- 1050 joule rating
- 6-ft. cord with molded right angle hospital-grade plug
- All metal housing

Applications

AC power distribution and surge suppression with hospital-grade receptacles and plug where durability and reliability are required. Not for use where NEC requires hospital-grade receptacles.

Package Includes

- AL-81561 Surge Suppressor
- Instruction manual with warranty information

Description

Our AL-81561 surge suppressor provides 6 hospital-grade outlets and protection from damaging surges and spikes with the added benefit of a convenient right-angle hospital-grade plug. The new design provides another option for convenient outlets outside the patient care area, including those tight spaces.

Features

- 1050-joule AC surge suppression rating
- Rugged all-metal housing withstands years of use without loss of ground path continuity
- 6 NEMA5-15R Hospital-Grade AC outlets
- 6-ft. AC cord with integrated, molded Hospital-Grade NEMA 5-15PHG plug
- Keyhole mounting tabs and flanges
- Switch safety cover prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120 volt, 50/60Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)
- UL1449 3rd Edition listed

Specifications

| OVERVIEW | |
|-------------------------|-----------------------|
| Intended Application | Hospital/Medical |
| Model Type | NOT For Patient Areas |
| OUTPUT | |
| Frequency compatibility | 50 / 60 Hz |

| | |
|------------------------------------|--|
| Output watts | 1800 |
| Circuit Breaker (amps) | 15 |
| Outlet quantity / type | 6 NEMA 5-15R-HG |
| Transformer accommodation | Supports 1 large transformer plug accessories without covering remaining outlets |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 120V (110-125V) |
| Input connection type | NEMA 5-15P-HG Right Angle Hospital-Grade |
| Input cord length (ft.) | 6 |
| Input cord length (m) | 4.6 |
| Voltage compatibility (VAC) | 120 |
| Maximum Surge Amps | 19500 |
| LEDS ALARMS & SWITCHES | |
| Diagnostic LEDs | LINE POWER PRESENT (green) |
| SURGE / NOISE SUPPRESSION | |
| AC suppression joule rating | 1050 |
| AC suppression response time | < 1 ns |
| Protection modes | Includes full normal mode surge suppression |
| Clamping voltage (RMS) | 140V |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Shipping Dimensions (HWD/in) | 2.25 x 15 x 6 |
| Shipping Dimensions (HWD/cm) | 5.7 x 38.1 x 15.24 |
| Shipping weight (lbs) | 3.5 |
| Shipping weight (kg) | 1.59 |
| Unit Dimensions (HWD/in) | 1.5 x 13.75 x 2.5 |
| Unit Dimensions (HWD/cm) | 3.81 x 34.9 x 6.35 |
| Unit weight (lbs) | 3.2 |

| | |
|-------------------------------------|--|
| Unit weight (kg) | 1.45 |
| Material of construction | Metal |
| Integrated keyhole mounting tabs | Includes keyhole mounting tabs and flanges |
| Receptacle Color | White |
| AC line cord color | Gray |
| Style | Strip |
| CERTIFICATIONS | |
| UL1449 3rd Edition (AC Suppression) | UL1449 3rd Edition |
| UL1363 (Power Tap) | UL1363 |
| cUL / CSA (Canada) | cUL |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

ALCO Sales. All rights reserved. All trademarks are the sole property of their respective owners. ALCO Sales has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.