

## NOT For Patient Areas - 6-outlet Power Strip with Hospital-Grade Plug & Receptacles & 6-ft. Cord

MODEL NUMBER. **AL-81563**



### Description

ALCO Sales AL-81563 power strip offers 15A capacity AC power distribution in a rugged, all-metal outlet strip for 120V applications. Features 6 hospital-grade receptacles, 6-ft. power cord and built-in 15A resettable circuit breaker. Switchless design prevents accidental shutoff. Optional use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 6 NEMA 5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60 Hz, 15A

FORMAT: all-metal corded multi outlet strip

### Features

- Rugged all-metal housing withstands years of use without breakage
- 6 x NEMA 5-15R-HG hospital-grade receptacles
- 6-ft. AC cord with integrated, molded NEMA 5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60 Hz electrical compatibility
- Certified by UL (USA) and cUL (Canada)

### Highlights

- Versatile power distribution strip
- 6 hospital-grade outlets and hospital-grade plug
- 6-ft. cord
- 15A resettable circuit breaker
- UL, cUL approved

### Applications

- AC power distribution with hospital-grade receptacles and plug where durability and reliability are required.
- Not for use where NEC requires hospital-grade receptacles.

### Package Includes

- AL-81563 Power Strip
- User manual with warranty information

## Specifications

OVERVIEW	
Intended Application	Hospital/Medical
Model Type	NOT For Patient Areas

OUTPUT	
Frequency compatibility	50 / 60 Hz
Circuit Breaker (amps)	15
Overload protection	15A circuit breaker
Outlet quantity / type	6 NEMA 5-15R-HG
Outlet orientation	Single row of 6
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	15A, 120V
Input connection type	NEMA 5-15P-HG
Input cord length (ft.)	6
Input cord length (m)	1.83
Voltage compatibility (VAC)	120
LEDS ALARMS & SWITCHES	
Switches	No power switch
PHYSICAL	
Shipping weight (lbs)	3.5
Shipping weight (kg)	1.6
Unit Dimensions (HWD/in)	1.5 x 13.75 x 2.5
Unit Dimensions (HWD/cm)	3.8 x 34.9 x 6.4
Unit weight (lbs)	2.4
Unit weight (kg)	1.1
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces
Receptacle Color	White
AC line cord color	White
Style	Strip
Outlets center to center measurement	38.7mm
Keyhole slot center to center measurement	Distance between keyhole tabs = 261.92mm; Distance between end tabs = 330.17
CERTIFICATIONS	

UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	Lifetime limited warranty

ALCO Sales. All rights reserved. All trademarks are the sole property of their respective owners. ALCO Sales has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.