

300W Medical-Grade Mobile Power Retrofit Kit with 36 Amp-hour Battery and 3 Outlets

MODEL NUMBER: AL-81613





Description

ALCO Save Medical-Grade Mobile Power Retroft KC provides UL 00001-1 compliance (a required patient attock-prevention measure) for all connected mobile electronic devices. The Mobile Power Retroft Ki kincludes everything needed to add AC power to medical carts. The kfS power supply features an isolation transformer that reduces the cumulative shock potential of connected equipment, helping to ensure UL 00001-1 compliance. The included 39 and how that their year does provide provides long-lasting mobile power. Included yearwheat Software saves valuable patient data from loss or comption if the cart is left unattended and battery power is depleted. The Mobile Power Retroft Kit also includes a remote user interface (RUI), mounting hardware and standard cabiling.

ALCO's Medical-Grade Mobile Power Retrofit Kit is fully compatible with most popular carts by AFC, Anthro, Datalux, GCX, Hergo, Humanscale, Jaco, Knurr, Stinger and more.

Features

- Provides UL 60601-1 compliance for connected mobile equipment (used in every sector of healthcare facilities, both inside and outside of patient-care areas)
- · Adds reliable mobile AC power source for medical carts
- Medical-Grade Mobile Power Supply (included) features an isolation transformer, providing UL 60601-1 compliance for connected equipment
- The Power Supply's advanced 3-stage charger recharges batteries faster and safer than conventional
 ...
- The Power Supply's internal Automatic Transfer Switch (ATS) allows the power supply to simultaneously run connected equipment while recharging the battery module
 The Power Supply also features 3 NEMA 5-154 AC outlets. a 10-ft. coiled AC input cord with a hospital-oracle
- In enviews supply also resurres a Neuron enter As Counters, a 10-ft, colled AL input cord with a nospital-gran NEMA 5-18ph plug, a USB communication port and a compact, all-metal housing that stands up to the most demanding environments

Highlights

- Provides UL 60601-1 compliance for connected mobile equipment (used in every sector of healthcare facilities, both inside and outside of patient-care areas)
- Adds reliable mobile AC power source to medical carts
 Saves money by upgrading new
- or existing non-powered carts for a fraction of the cost of buying new powered models
- Protects valuable patient data from loss or corruption
- Simultaneously powers connected equipment while recharging batteries
 Includes everything needed to
- retrofit a cart: mobile power supply, 36-amp hour user-replaceable battery module. PowerAlert data-saving software, remote user interface (RUI) and mounting hardware kit

Applications

 Medical-Grade mobile AC power supply for medical carts used in every sector of healthcare facilities—both inside and outside of patient-care areas. Provides mobile power and UL 60601-1 compliance for a variety of cart-mounted electronic devices: computers (laptop or desktop), scanners, diagnostic equipment and more.

Package Includes

Medical-Grade Mobile Power

Supply

- 36-amp hour user-replaceable
 Battery Module and cabling
- PowerAlert Data-Saving Software



Specifications

- 36-amp hour user-replaceable Battery Module (included) provides long-lasting mobile power. Maintenance-free spill-/leak-proof sealed lead-acid (SLA) AGM battery features simple plug-in connection with included cable
- Power/Alert Data-Saving Software (included) automatically saves valuable patient data from loss or corruption if the cart is left unattended and hattery power is depleted. Included cable connects the Power Supply to any cart-mounted computer (desktop or laptop)
- alarm-mute switches. Mounts anywhere on the cart for easy access with included mounting material and cable . Mounting Hardware Kit retrofits most standard medical carts from AFC, Anthro, Datalux, GCX, Hergo, Humanscale, Jaco, Knurr, Stinger and more
- . Remote User Interface (RUI) displays output and battery charge status at a plance. Includes on/off and

CD and USB cable

- Remote User Interface (RUI) and cabling
- . Mounting Hardware Kit and owner's manual with warranty information

OVERVIEW Intended Application Hospitals & Medical Facilities OUTPUT Frequency compatibility 60 Hz Output watts 300 Continuous output capacity (watts) 300 Peak output capacity (watts) 750 Output nominal voltage 120V Outlet quantity / type 3 NEMA 5,15D INPUT 120V AC Nominal Input Voltage(s) Supported Recommended Electrical Service 15A, 120V Input connection type NEMA 5-15P-HG Hospital-Grade Input cord length (ft.) 10 3.05 Input cord length (m) Voltage compatibility (VAC) BATTERY DC system voltage (VDC) Battery charge Equal to discharge time. Includes advanced 3-stage (10A) battery charges LEDS ALARMS & SWITCHES Alarms Low Battery Alarm Switches On Remote User Interface (RUI): On/Off Switch and Alarm-Mute Switch



Front panel LEDs	On Remote User Interface (RUI): Output AC Power, Battery Charge Level and Battery Charging Status
SURGE / NOISE SUPPRESSION	
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Shipping Dimensions (HWD/in)	13 x 24 x 26
Shipping Dimensions (HWD/cm)	33.02 x 60.96 x 66.04
Shipping weight (lbs)	72.4
Shipping weight (kg)	32.8
Cooling method	Fan
Material of construction	Power Supply and Battery Module: metal
Style	Heavy-duty with built-in battery charger
Form factors supported	Retrofits most standard medical cart configurations
COMMUNICATIONS	
Network monitoring port	USB
Software and cabling included	PowerAlert Data-Saving Software CD and USB cable
SPECIAL FEATURES	
Remote control capability	Yes
CERTIFICATIONS	
Certifications	Tested, certified and compliant to UL 60601-1, CAN/CSA-C22.2 No. 601.1-M90 and UL 1778 by TUV
WARRANTY	
Product Warranty Period (Worldwide)	2-year power module and 6-month battery module limited warranty



More information, including related products, owner's manuals, and additional technical specifications, can be found online at: www.alcosales.com

ALCO Sales Lite. All rights reserved. All trademarks are the sole property of their respective owners. ALCO Sales has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.