

## BERKELEY SPRING BATHING SYSTEM

The Berkeley Springs Bathing System provides a unique combination of function, safety, and comfort. The low threshold and wide side-entry door allows easy access for residents with various degrees of mobility and the built-in contoured seat allows the resident to sit comfortably and safely in a slightly reclined position. The Berkeley Springs Bathing System has an attractive, sleek exterior design giving the bathing area an upscale look. Caregivers will enjoy the unit for its ease of use and the improved quality of care they can provide to the resident.

	WEIGHT OF THE
AL-82891	Side-Entry with Thermostatic Mixing Valve WEIGHT CAPACITY
AL-82892	Side-Entry with Thermostatic Mixing Valve and Disinfectant System
AL-82893	Side-Entry with Thermostatic Mixing Valve, Disinfectant System, and Air Spa
AL-82894	Bath Lift
AL-82895	Side-Entry with Thermostatic Mixing Valve with Bath Lift
AL-82896	Side-Entry with Thermostatic Mixing Valve and Disinfectant System with Bath Lift
AL-82897	Side-Entry with Thermostatic Mixing Valve, Disinfectant System, and Air Spa
	with Bath Lift

## FEATURES:

- Thermostatic mixing valve Provides an anti-scald protection that dispenses 15 gallons per minute for fast tub fill.
- ♦ Built-in disinfection system The most time-efficient solution for disinfection of the bath's external surfaces and minimizes the risk of cross-infection. The built-in disinfection system cabinet is conveniently located on the front of the tub for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.
- ♦ Handheld shower wand Hair and upper body washing can be used at the same time the tub is filling.
- Water temperature display Monitors tub-fill and shower wand temperatures.
- 3/4" supply lines Constructed of stainless steel mesh clad.
- ♦ Lap and shoulder harness Used for resident safety.
- ♦ Secondary Door Latch Prevents accidental door opening when in use.
- ♦ The CleanDrive Air Spa System Variable speeds and pulse modes designed to enhance the bathing experience for the resident and caregiver.

## Additional features of the CleanDrive Air System include:

- ♦ The hydro massage provides millions of preheated air bubbles in the water which increases stimulation of peripheral blood circulation, reduces pain and inflammation in the joints, gently massages away dirt, and induces deeper relaxation.
- ♦ The CleanDrive Air Spa System is a hygienic and low maintenance hydro massage system featuring 12 air jets with spring loaded check valves for back flow prevention. It prevents water from entering the air lines eliminating the extra step to disinfect air lines. The CleanDrive Air Spa System simplifies disinfection and reduces the possibility of cross-contamination.
- Unlike most other whirlpool and air spa systems, the CleanDrive Air Spa System does not allow water to enter the air lines to reduce the growth of bacteria and mold.
- The motor is quiet, efficient, and has a ceramic heating element that blows warm air to help maintain the water temperature and warm the surface of the tub.
- Warranty: 5 Years on finishes and composite shell, 3 years on all moving and stationary parts and lifetime on the door seal.





For your dependent residents, the Berkley Spring is specifically designed for use with the Berkley Spring Bath Lift, which provides seamless transfers from bed-to-bath in a comfortable and safe seated position.

The wide side-entry door and unobstructed mobile lift access will allow the resident to enter and exit the bathtub easily and safely.













The built-in disinfection system cabinet is conveniently located on the front side of the tub for easy access. The lockable cabinet provides a secure place for cleaning supplies and disinfectants.

Made in the USA

## SPECIFICATIONS

Length (outside dimension):	60.75"
Width (outside dimension):	33"
Length (inside dimension):	49"
Width (inside dimension):	27"
Height (to top of console):	43"
Height (to top of door):	36.5"
Seat Height:	18" (measured from floor)
Seat Width:	26"
Threshold Height:	13" (measured from floor)
Transfer Device Access:	7" H x 44" W
Water Supply Inlet:	3/4" diameter
Drain Size:	1.5"
Water Capacity (Occupied):	52 gallons
Fill Time:	3 minutes, 28 seconds
Drain Time:	2 minute, 30 seconds
Weight Capacity (resident):	600 lbs
Door Configuration:	Right Hinge only
Electrical Supply:	115V AC; 60Hz; 15 amp

Phone: 800-323-4282 Fax: 800-950-1167



Like us on Facebook at: facebook.com/ALCOSalesServiceCo



info@alcosales.com www.alcosales.com