

External 24V 2U Rack/Tower Battery Pack for select Tripp Lite UPS Systems (AL-84129)

MODEL NUMBER: AL-84129



Highlights

- Extends the runtime of expandable 24V DC Tripp Lite UPS Systems
- Supports 2U rackmount installation; 4 post installation accessories included
- Options for 2 post rackmount, tower and wallmount installation available

Package Includes

- AL-84129 external battery pack with attached DC cabling 4 post
- compatible rack mounting hardware
- Owner's manual

Description

The AL-84129 rack/tower external battery pack offers extended battery runtime when used in conjunction with expandable 24V Tripp Lite rackmount and tower UPS systems. Includes heavy gauge cabling with high current DC connector for safe, simple installation. Included mounting accessories support 2U rackmount installation in 4 post racks. Options for 2-point front-rail mounting, 2 post center-mounting, wallmount and upright tower installation available.

Features

- Offers extended-run UPS operation when used in conjunction with compatible 24V DC Tripp Lite UPS systems
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Included mounting brackets support rackmount installation in 4 post racks using only 2 rack spaces(2U)
- UPDHDEARKIT option supports 2 point front-rail rackmount installation without rear supports
- AL-84125 option supports balanced 2 point center-mounting in 2 post equipment racks
- AL-84125 option also enables wallmount installation
- AL-84123 option enables upright tower placement
- NOTE: LIMIT OF 1 AL-84129 PER UPS, SEE AL-84131 or AL-84130 FOR MULTI-PACK COMPATIBILITY

Specifications

BATTERY	
DC System Voltage (VDC)	24
UPS Connection	Attached cable with red/black 75 amp male DC connector

Typical Battery Lifespan	4-6 years typical (North America)
PHYSICAL	
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount
Installation Form Factors Supported with Optional Accessories	2 post rackmount(AL-84125); Wallmount(AL-84125); Tower(AL-84123); 2-4 post front rail rackmount(UPSHDEARKIT)
Minimum Required Rack Depth (inches)	17
Minimum Required Rack Depth (cm)	43.18
Shipping Dimensions (hwd / in.)	9 x 23.75 x 20.25
Shipping Dimensions (hwd / cm)	22.9 x 60.3 x 51.4
Shipping Weight (lbs.)	64.3
Shipping Weight (kg)	29.2
Unit Dimensions (hwd / in.)	3.5 x 17.5 x 14
Unit Dimensions (hwd / cm)	8.9 x 44.5 x 35.6
Unit Weight (lbs.)	53.9
Unit Weight (kg)	24.45
Material of Construction	Steel
External Battery Pack Form Factor	Rack/Tower
Minimum Required Rack Depth (mm)	432
CERTIFICATIONS	
Certifications	CE
WARRANTY	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty

