

External 24V 2U Rack-Mount Battery Pack for select Tripp Lite UPS Systems (AL-84130)

MODEL NUMBER: AL-84130



Highlights

- Extends the runtime of expandable 24V DC Tripp Lite UPS Systems
- Included daisychain connector supports the addition of multiple compatible external battery packs
- Supports 2U rackmount installation; 4 post installation accessories included
- Options for 2 post rackmount installation available

Package Includes

- AL-84130 external battery pack with attached DC cabling 4 post
- compatible rack mounting hardware
- Owner's manual

Description

The AL-84130 rackmount external battery pack offers extended battery runtime when used in conjunction with expandable 24V Tripp Lite rackmount UPS systems. Includes heavy gauge cabling with high current DC connector for safe, simple installation. Included daisychain connector enables the connection of additional compatible 24V external battery packs to the host UPS. Included mounting accessories support 2U rackmount installation in 4 post racks. Options for 2-point front-rail mounting, 2 post center-mounting and wallmount installation available.

Compatible with these UPS Systems - AL-84114, AL-84109 and other Tripp Lite UPS systems that specify the use of this battery pack.

Features

- Offers extended-run UPS operation when used in conjunction with compatible 24V DC Tripp Lite UPS systems
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Daisychain connector enables the connection of additional compatible 24V external battery packs to the host UPS
- Included mounting brackets support rackmount installation in 4 post racks using only 2 rack spaces(2U)
- UPDHDEARKIT option supports 2 point front-rail rackmount installation without rear supports
- AL-84125 option supports balanced 2 point center-mounting in 2 post equipment racks

Specifications

BATTERY	
DC System Voltage (VDC)	24
UPS Connection	Attached cable with red/black 75 amp DC connector
Typical Battery Lifespan	4-6 years typical (North America)

PHYSICAL	
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount
Installation Form Factors Supported with Optional Accessories	2 post rackmount(AL-84125); 2-4 post front rail rackmount(UPSHDEARKIT); Wallmount(AL-84125)
Optional Mounting Accessory Notes	Wallmount installation using AL-84125 requires that the plastic front bezel of the battery pack face upward
Minimum Required Rack Depth (inches)	16.8
Minimum Required Rack Depth (cm)	42.67
Shipping Dimensions (hwd / in.)	8.5 x 21.5 x 23.2
Shipping Dimensions (hwd / cm)	21.6 x 54.6 x 58.9
Shipping Weight (lbs.)	71.1
Shipping Weight (kg)	32.3
Unit Dimensions (hwd / in.)	3.4 x 17.3 x 13.8
Unit Dimensions (hwd / cm)	8.6 x 7.9 x 35
Unit Weight (lbs.)	59.4
Unit Weight (kg)	26.94
Material of Construction	Steel
External Battery Pack Form Factor	Rack
Minimum Required Rack Depth (mm)	427
WARRANTY	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty

