

## Portable Charger - 2x USB-A, 12,000mAh Power Bank, Lithium-Ion, Auto Sensing, Black

MODEL NUMBER: AL-89240-12



Compact 2-port 12,000mAh power bank charges multiple smartphones, tablets, e-readers, MP3 players and other handheld mobile devices anywhere, anytime, without plugging into an AC power outlet.

### Description

No more frantic searching for an AC power outlet when your mobile device's battery power is getting low. The high-capacity AL-89240-12 12,000mAh Dual-Port Mobile Power Bank is an ideal power solution when you're on the road or stuck somewhere without convenient electricity. The portable dual-USB battery charger weighs barely half a pound, and fits comfortably in your purse or backpack to keep your phone, tablet, e-reader, MP3 player, digital camera or other handheld device operating when you need it.

Just connect your devices to the AL-89240-12's USB-A ports using the included USB Micro-B cable and/or another cable suitable for your device. The devices will begin charging immediately. Press the on/off button to monitor the power bank's battery capacity via the easy-to-read LEDs and know how much charge is available.

The dual USB ports provide up to 5V 2.4A of power, so you can charge two devices at once. In addition, both ports benefit from auto-sensing technology that identifies how much amperage the connected device is designed to take and adjusts its charging accordingly.

The lithium-ion battery's hearty 12,000mAh capacity charges devices at maximum power draw for hours. It protects against short circuits, overvoltage, overcurrent, overcharges and overdischarges for safe, reliable charging. To charge the AL-89240-12, connect the USB Micro-B port to a USB charger or a computer's USB port using the included cable.

### Features

#### Travel-Sized for Convenient Charging of Dual Devices Anywhere

- Compact form fits comfortably in your purse or backpack

### Highlights

- Dual USB-A ports provide up to 5V 2.4A of power
- Auto-sensing port adjusts amperage to match connected device
- LEDs indicate remaining battery capacity at a glance
- 3 ft. USB Micro-B charging cable included
- Compact form fits comfortably in your purse or backpack

### Package Includes

- AL-89240-12 12,000mAh Dual-Port Mobile Power Bank USB Battery Charger
- USB Micro-B cable, 3 ft.
- Owner's manual

- Ideal for charging up to 2 smartphones, tablets, e-readers, MP3 players and other handheld mobile devices simultaneously
- Works with Android, Apple and Windows devices

#### **Built-In 12,000mAh Lithium-Ion Battery Charges Without an AC Power Outlet**

- Charges at maximum power draw for hours to ensure your devices are ready when you need them
- Dual USB ports provide up to 5V 2.4A of power
- Auto-sensing ports adjust amperage to match amperage of connected device
- Protects against short circuits, overvoltage, overcurrent, overcharges and overdischarges

#### **Easy to Recharge for the Next Time You Leave Home or Office**

- USB Micro-B port connects to USB charger or computer's USB-A port to charge internal battery
- Built-in LEDs indicate at a glance how much battery capacity is left
- 3 ft. USB Micro-B charging cable included

## Specifications

<b>OVERVIEW</b>	
UPC Code	037332203939
Product Type	Portable Charger
Charging Form Factor	Portable
Device Compatibility	Phone; Tablet; Amazon Kindle
Over Current Protection	Yes
Technology	USB
<b>INPUT</b>	
Nominal Input Voltage(s) Supported	5V DC
Input Plug Type	USB MICRO-B (FEMALE)
Input Plug Type Detail	USB-A to USB Micro B cable provided
<b>OUTPUT</b>	
Overload Protection	Yes
<b>CHARGING</b>	
Charging Ports / Amps	(2) 2.4A
Number of Charging Ports	2
Total Charging Amps	2.4A
Charging Method	USB

Total Charging Watts	12
Charging Ports Detail	USB-A: 5V/2.4A
Charging Port Type	(2) USB A (FEMALE)
Charging Method Detail	12,000 mAh
<b>PHYSICAL</b>	
Color	Black
Material of Construction	ABS
Unit Dimensions (hwd / cm)	14 x 6.4 x 2.5
Unit Dimensions (hwd / in.)	5.5 x 2.5 x 1
Unit Weight (kg)	0.27
Unit Weight (lbs.)	0.60
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32 to 113 F ( 0 to 45 C )
Storage Temperature Range	5 to 113 F ( -15 to 45 C )
Relative Humidity	0% to 90% RH, Non-Condensing
<b>CONNECTIONS</b>	
Side A - Connector 1	MICRO-USB B (FEMALE)
Side B - Connector 1	(2) USB A (FEMALE)
Connector Plating	Nickel
Contact Plating	Nickel
<b>SPECIAL FEATURES</b>	
Overcurrent Protection	Yes
Overvoltage Protection	Yes
GaN Technology	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Certifications	Tested to FCC, CE, ROHS
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	1-year limited warranty