

PARTNERING TO SAVE YOU TIME, ENERGY & MONEY!

U1LiFe™ Series U1-40
12V, 40Ah Battery

- Lightweight, drop-in replacement for U1 size, 12 Volt, Sealed Lead Acid (SLA) battery applications
- Highly reliable, robust, long-life, Iron Phosphate, rechargeable battery solution
- Safest and most environmentally-friendly battery chemistry available today






AL-82821
Call for Custom Quote

Why U1LiFe™?

- Increased life cycles up to 10 times over Sealed Lead Acid batteries
- Three times the reduction in weight over conventional SLA battery offerings
- Zero maintenance
- Reduces technician replacement cost
- Fast recharge enables increased productivity and uptime of carts
- Potential capital reduction through increased equipment utilization

Low Total Cost of Ownership*
*(48% cost saving per battery**)*

	Sealed Lead Acid Battery	U1LiFe Battery
Run Time <i>(Based on chemistry energy density)</i>		 2x Run Time
Cycle Life <i>(100% DOD)</i>	250 Cycles	2,000+ Cycles
Lifespan <i>(Based on daily use)</i>	<1 year	5+ years
Weight		1/3 Weight

*Conversion charts available @ www.alcosales.com

**Estimated total cost of ownership based on 5-year span

Applications

- Patient Monitoring: Mobile & Portable Ultrasound, Medical Carts, Portable X-Ray
- Compatible with all Medical Cart brands that feature the following Triplite inverter systems:
 - HC150SL
 - HCINT150SL
 - HC120DC

Features

- Iron Phosphate Lithium-Ion Technology
- Built-In SMBus Battery Management System
- Dual RJ45 Connection Ports
- LED Status Indicator
- Battery Protection Circuitry
- Cell Balancing Circuitry
- Long Cycle Life

Safety / Agency Information

All U1 series batteries have been certified to the following safety and performance standards:

- UN38.3
- UL2054
- IEC62133
- EN60601-1-2

**Copies of the certifications are available upon request*



Specifications	U1-40
Nominal Voltage	12.8 Volts
Nominal Capacity	38.4 Amp Hour (491.52Wh)
Continuous Discharge Current	20 Amps
Pulse Discharge Current	110 Amps <15ms, 300 Amps<827µs (@ 25°C)
Operating Temperature Range	-20° C to +60°C
Storage Temperature Range	-40° C to +60°C
Maximum Charge Voltage	14.4 Volts
Float Voltage Charge	13.8 Volts
Max Charging Current @ 25°C	20 Amps
Weight	4.7Kg
Dimensions (L x W x H)	209 x 137 x 185mm
Communication	SMBus
Operating Humidity	20% - 80%
Shipping Classification	Class 9
Battery Terminals	1/4-20 Female Thread
Case Flame Rating	UL-94 V-0

Video demonstrations, Total Cost of Ownership charts and other technical data available at www.alcosales.com or by calling 1-800-323-4282

Manufactured By:

ICCNexergy, Inc.
4 Westbrook Corporate Center
Suite 900, Westchester, IL 60154

800-210-1431
www.iccnexergy.com



ICCN_ALCO-SS_U1LiFe_032415_01



U1LiFe™ Series
Medical Cart Batteries

Distributed By:

ALCO Sales & Service Co.
6851 High Grove Blvd.
Burr Ridge, IL 60527

800-323-4282
www.alcosales.com

